



Il colore italiano dal 1831

# CLEARCOAT

## TECHNICAL DATA SHEET

COD. 7AD025-7AD026





### WATER-BASED 1-COMPONENT PROTECTIVE CLEARCOAT

- Protective clearcoat, available in matte and gloss versions, based on polyurethane polymers in a water dispersion, featuring high hardness and excellent adhesion. Non-yellowing and resistant to aggressive external agents, including UV radiation, thanks to protective filters contained in the product. Offers excellent protection for decorative products against surface stress, without altering their appearance and metallic effect.

### TYPICAL CHEMICAL AND PHYSICAL CHARACTERISTICS

APPEARANCE	Matte / Gloss
COMPOSITION	Special modified acrylic polyurethane binders
BROOKFIELD VISCOSITY	1,500 ± 200 cP G3 V20 at 70°F
GLOSS	Matte: 40 / Gloss: 90 units at 60°
C.O.V. / V.O.C	Max. 100 g/L (0.83 lbs/gal).
COLOR	Neutral

### TYPICAL APPLICATION CHARACTERISTICS

	EFFECTIVE COVERAGE	350-450 sq ft / U.S. gal depending on the substrate
	DRYING (at 70°F and 65% H.R.)	Touch dry: 30 min For re-coating: 3-4 hours* Fully dry: 24 hours
	DILUTION	Roller, brush: ready to use Spray: 10-20% with water
	TOOLS	Roller, brush, spray

### APPLICATION SYSTEM

**SUBSTRATES:** Paints, decoratives effect.

**SUBSTRATE PREPARATION:** Substrates must be sound, dry, clean, firm and free of damp patches and traces of dirt, grease, mold, etc. Remove flaking or chalky old paintwork by brushing or sanding. Serious imperfections, deficiencies, cracks and peeling must be removed and filled with Boero Water-Resistant Gypsum Powder.

**In the case of chalky paints and surfaces, prepare the substrate with suitable fixative primer.**



**Il colore italiano dal 1831**

# CLEARCOAT

COD. 7AD025-7AD026

## RECOMMENDED APPLICATION TECHNIQUE

Apply two coats of product to the decorated surface, leaving at least 3-4 hours\* between one coat and the next. In condition of high humidity the above time may increase), between one coat and the next. Stir the product carefully

## GENERAL INFORMATION AND NOTICES

Clean tools immediately after use with water.

Keep the product in a cool place and do not allow to freeze. Do not apply at temperatures below 40°F.

*The technical information provided above is the result of careful laboratory testing and practical experience. Nevertheless, as the product is often used outside our control, we are unable to guarantee the quality of the end result. This information is subject to review by the Company. Please carefully read the "GENERAL RECOMMENDATIONS".*

CQ Rev. 1 - September 2018



**Boero USA, Inc.**  
1209 Orange Street  
Wilmington, DE 19801  
800 935-6596  
[www.boerousa.com](http://www.boerousa.com)

MADE IN ITALY