



Il colore italiano dal 1831

GYPSUM POWDER (WATER RESISTANT)

TECHNICAL DATA SHEET
COD. 7US003

STUCCO IN POWDER FORM FOR SKIM COATING AND USE AS A FILLER

- White lime cement-based stucco in powder form for use as a filler and for skim coating walls, traditional or premixed plaster, plaster panels, plasterboard, fiber cement, etc.
- Featuring good adhesion and mechanical resistance, the product can fill thicknesses up to 3 mm (100-120 mil) in one pass.

CHEMICAL AND PHYSICAL CHARACTERISTICS

APPEARANCE	Powder
COMPOSITION	Special lime cement-based hydraulic binders; selected additives
C.O.V. / V.O.C	Max. 100 g/L (0.83 lbs/gal)
PACK	Paper bags
COLOR	White

TYPICAL APPLICATION CHARACTERISTICS

	EFFECTIVE COVERAGE	0.25 lb/ft² on smooth substrates variable depending on the conditions and roughness of the substrate
	DRYING (at 70°F and 65% H.R.)	Touch dry: 1-2 hours Fully dry: 24 hours
	MIXING RATIO	Add 1 parts of water to 2 parts of product
	TOOLS	Stainless steel finishing trowel and spatula

APPLICATION SYSTEM

SUBSTRATES: Civil plaster, plasterwork, plasterboard, skim-coated walls, wood, etc., suitably prepared.

SUBSTRATE PREPARATION: Substrates must be sound, dry, clean, firm and free of damp patches and traces of dirt, grease, mold, etc. Remove flaking or chalky old paintwork by brushing or sanding.

In the case of chalky paint and surfaces, prepare the substrate with suitable fixative primer.



Il colore italiano dal 1831

GYPSUM POWDER (WATER RESISTANT)

COD. 7US003

RECOMMENDED APPLICATION TECHNIQUE

Mix a bag or the quantity of stucco powder necessary with clean water in the ratio indicated above, using an electric stirrer to obtain a smooth paste. Leave to rest for five minutes and stir again, then apply evenly with a finishing trowel, using vertical and horizontal strokes.

Apply subsequent layers when the layer beneath is still not perfectly dry.

Mix carefully using a mechanical stirrer. The useful life of the paste is about 120 minutes. Do not add water or stir the product again after this period has elapsed.

GENERAL INFORMATION AND NOTICES

Clean tools immediately after use with water.

Keep the product in a cool place and do not allow to freeze. Do not apply at temperatures below 40°F.

Shelf life in closed bags and stored in a dry place is at least 12 months.

The technical information provided above is the result of careful laboratory testing and practical experience. Nevertheless, as the product is often used outside our control, we are unable to guarantee the quality of the end result. This information is subject to review by the Company.

Please carefully read the "GENERAL RECOMMENDATIONS".

CQ Rev. 1 - October 2018



Boero USA, Inc.
1209 Orange Street
Wilmington, DE 19801
800 935-6596
www.boerousa.com

MADE IN ITALY