



Il colore italiano dal 1831

STAIN RESISTANT TEXTURE

TECHNICAL DATA SHEET
COD. 7AD027





PRODUCT IN PASTE FORM FOR INTERIORS

- Stucco in ready-to-use paste form for interiors, featuring excellent applicability, optimum resistance to dirt and high elasticity.
- With its remarkable workability, the product can be used to obtain an infinite range of textures using different tools and application methods. Particularly suitable for decorating substrates with crazing problems caused by joints, seams and/or similar situations.
- Can be re-coated with other decorative effects (e.g. Metallic paint) and/or protective varnishes (e.g. Clearcoat).

CHEMICAL AND PHYSICAL CHARACTERISTICS

APPEARANCE	Matt
COMPOSITION	Special acrylic binders; selected fillers
BROOKFIELD VISCOSITY	60,000 ± 5,000 cP G7 V20 at 70°F
C.O.V. / V.O.C	Max. 100 g/L (0.83 lbs/gal).
COLOR	White. Can be tinted using tinting systems

TYPICAL APPLICATION CHARACTERISTICS

	EFFECTIVE COVERAGE	100-150 sq ft / U.S. gal depending on the substrate and the thickness applied
	DRYING (at 70°F and 65% H.R.)	Touch dry: 1-2 hours For re-coating: 6-8 hours Fully dry: 24 hours
	DILUTION	Ready to use
	TOOLS	Roller, brush, Boero stainless-steel flex trowel

APPLICATION SYSTEM

SUBSTRATES: Civil plaster, plasterwork, plasterboard, skim-coated walls, wood, etc., suitably prepared.

SUBSTRATE PREPARATION: Substrates must be sound, dry, clean and as smooth as possible. Tape off adjacent surfaces with the proper low tack tape. Patch serious imperfections, deficiencies, etc. with Boero Water-Resistant Gypsum Powder.

In the case of chalky paint and surfaces, prepare the substrate with suitable fixative primer.



Il colore italiano dal 1831

STAIN RESISTANT TEXTURE

COD. 7AD027

APPLICATION OF BASECOAT

Apply 2 coats of Micro Gritty primer or a egg-shell paint in a similar color to the *Boero Stain Resistant Texture* color.

APPLICATION OF STAIN RESISTANT TEXTURE (See website for How-To Videos www.boerousa.com)

The *Boero Stain Resistant Texture* is an Elastomeric Fine Stucco that can be applied using a microfiber roller, then Back-Troweled, Back-Brushed, Embossed with Texture Rollers, etc., or Troweled directly to the surface. Product is ready to use. 1 or 2 coats are advised. (2 coats for full coverage, with "Smooth Effect" as the 1st layer)

Smooth Effect, Roll & Back-Trowel: Using a microfiber mini roller in corners and edges and a 9" microfiber roller in the large areas, apply the *Boero Stain Resistant Texture* in random rolled directions, (up, down and diagonally, creating random "curving X's"). Immediately "Back-Trowel" randomly using a *Boero Stainless-Steel Flex Trowel* to create a smooth, random pattern. (This layer can be used as the 1st coat in a 2-coat finish).

Criss Cross Pattern & Textures: Using a microfiber mini roller in corners and edges and a 9" microfiber roller in the large areas, apply the *Boero Stain Resistant Texture* in random rolled directions (up, down and diagonally, creating random "curving X's"). Immediately "Back-Trowel" randomly using a *Boero Stainless-Steel Flex Trowel* to create the desired random pattern.

Textile Effect, Roll & Back Brush: Using a microfiber mini roller in corners and edges and a 9" microfiber roller in the large areas, apply the *Boero Stain Resistant Texture* in vertical directions. Immediately Back-Brush through the product in vertical for a Striae effect. Immediately Back-Brush through the product in vertical and then randomly in horizontal direction for a **Textile Effect**.

GENERAL INFORMATION AND NOTICES

Clean tools immediately after use with water.

Keep the product in a cool place and do not allow to freeze. Do not apply at temperatures below 40°F.

The technical information provided above is the result of careful laboratory testing and practical experience. Nevertheless, as the product is often used outside our control, we are unable to guarantee the quality of the end result. This information is subject to review by the Company.

Please carefully read the "GENERAL RECOMMENDATIONS".



Boero USA, Inc.
1209 Orange Street
Wilmington, DE 19801
800 935-6596
www.boerousa.com

CQ Rev. 2 - October 2018

MADE IN ITALY