



Il colore italiano dal 1831

VENETIAN PLASTER

TECHNICAL DATA SHEET

COD. 7AD028





DECORATIVE PRODUCT IN PASTE FORM FOR INTERIORS

- Decorative product in paste form, ready for use in interiors to obtain highly decorative finishes that are resistant to washing and dirt.
- Features excellent applicability and workability, plus good retouching.
- Therefore, in the case of surface damage, the part in question can be restored without leaving any particular sign of the defect on the surface after the repair. Excellent water repellency, low dirt pick-up.

TYPICAL CHEMICAL AND PHYSICAL CHARACTERISTICS

| | |
|-----------------------------|--|
| APPEARANCE | Matt - semi gloss |
| COMPOSITION | Special acrylic binders, selected fillers |
| BROOKFIELD VISCOSITY | 80,000 ± 5,000 cP G7 V20 at 70°F |
| C.O.V. / V.O.C | Max. 100 g/L (0.83 lbs/gal) |
| COLOR | White. Can be tinted using tinting systems |

TYPICAL APPLICATION CHARACTERISTICS

| | | |
|---|---|--|
|  | EFFECTIVE COVERAGE | 100-200 sq ft / U.S. gal for three coats depending on the substrate and thickness applied |
|  | DRYING (at 70°F and 65% H.R.) | Touch dry: 1-2 hours Fully dry: 24 hours |
|  | DILUTION | Ready for use |
|  | TOOLS | Roller, Boero stainless-steel flex trowel and Boero stainless-steel prepared trowel |

APPLICATION SYSTEM

SUBSTRATES: Civil plaster, plasterwork, plasterboard, skim-coated walls, wood, etc., suitably prepared.

SUBSTRATE PREPARATION: Substrates must be sound, dry, clean and as smooth as possible.

Tape off adjacent surfaces with the proper low tack tape. Patch serious imperfections, deficiencies, etc with Boero Water Resistant Gypsum Powder.



Il colore italiano dal 1831

VENETIAN PLASTER

COD. 7AD028

APPLICATION OF BASECOAT

Apply Micro Gritty Primer or a flat paint in a similar color to the *Boero Venetian Plaster*.
Chalky paints and surfaces, prepare the substrate with suitable fixative primer.

APPLICATION OF VENETIAN PLASTER (See website for How-To Videos www.boerousa.com)

The *Boero Venetian Plaster* can be applied using a microfiber roller, then Back-Troweled or Troweled directly to the surface. Product is ready to use. A minimum of 3 coats is recommended.

1st Coat - Roller & Back-Trowel: Using a microfiber mini roller in corners and edges and a 9" microfiber roller in the large areas, apply the *Boero Venetian Plaster* in random rolled directions (up, down and diagonally, creating random "curving X's"). Immediately "Back-Trowel" randomly using a *Boero Stainless-Steel Flex Trowel* to create the random pattern.

Trowel: You may apply the *Boero Venetian Plaster* directly to the surface using a *Boero Stainless-Steel Flex Trowel* in a random "X" to create your desired pattern.

2nd Coat - Trowel: Apply the *Boero Venetian Plaster* directly to the surface using a *Boero Stainless-Steel Flex Trowel* in a random "X" to fill in and smooth the texture.

3rd Coat - Trowel: Apply the *Boero Venetian Plaster* directly to the surface using a *Boero Stainless-Steel Flex Trowel* in a random "X" to fill in and smooth the texture. Skim tightly. (For the highest sheen, when completely dry, sand the surface with 3000 grit sanding pad prior to final burnishing step.)

4th Step: Burnish/Polish/Compress: When the *Boero Venetian Plaster* is dry or nearly dry, create your desired level of sheen by burnishing/polishing/compressing using a *Boero Stainless-Steel Prepared Trowel* in random directions.

GENERAL INFORMATION AND NOTICES

Clean tools immediately after use with water.

Keep the product in a cool place and do not allow to freeze. Do not apply at temperatures below 40°F.

The technical information provided above is the result of careful laboratory testing and practical experience. Nevertheless, as the product is often used outside our control, we are unable to guarantee the quality of the end result. This information is subject to review by the Company.

Please carefully read the "GENERAL RECOMMENDATIONS".



Boero USA, Inc.
1209 Orange Street
Wilmington, DE 19801
800 935-6596
www.boerousa.com

CQ Rev. 2 - October 2018

MADE IN ITALY